



# 1060nm Polarization Maintaining Optical Circulator



## Features

- Low Insertion Loss
- High Isolation
- High Extinction Ratio
- High Stability and Reliability
- Cost Effective

## Applications

- Optical Fiber Amplifier
- Pump Laser Source
- Fiber Optic Sensor
- Test and Measurement
- Instrumentation

## Performance Specifications

Parameter	Specification
Operating Wavelength(nm)	1050~1070
Typical Peak Isolation(dB)	25
Minimum Isolation (dB)	20
Typical Insertion Loss(dB)	1.3
Maximum Insertion Loss(dB)	1.8
Return Loss (dB)	50
Cross Talk (dB)	Min. 45 (Typ. 50)
Extinction Ratio	Max. 20 (Typ. 25)
Wavelength Dependent Loss(dB)	0.2
Operating Temperature (°C )	0 ~ +65
Storage Temperature (°C )	40 ~ +85
Fiber Type	See Order Information
Power Handling(mW)	400
Dimensions (mm)	L62.6xW28xH27

1. The PM fiber and the connector key are aligned to the slow axis.
2. The ER is for fiber  $\leq 0.75$  meter. Increase fiber length can decrease the ER.
3. For devices with connectors, insertion loss will be 0.3dB higher, return loss will be 5dB lower, and extinction loss will be 2dB lower.

## Ordering Information

PMOC	<input type="checkbox"/>	<input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/> <input type="checkbox"/>
	Port	Wavelength	Grade	Pigtail Style	Fiber Length	Fiber Type	In/Out Connector
	3=3 Port	1060=1060nm	P=P Grade	1=Bare Fiber 2=900um Jacket	1=0.25m 2=0.5m 3=1.0m S=Custom Length	2=PM 980 S=Special	0=None 1=FC/APC 2=FC/PC 3=SC/APC 4=SC/PC 5=ST 6=LC X=Special

## Dimensions (mm)

